

BoxLine Eco Pro



SlimLine Uitvoering
Slagvast - Waterdicht
ABS-PC

BoxLine Eco Pro 60 - 120

Model : BoxLine Single 60
Artikelnummer : 93060/61/65
Aansluiting : 230VAC
Venster : prismatisch mat
Vermogen : 8watt
Power Factor : >0.9
Lichtroom : 720lm
Ra : >80
Lichtkleur : 3000/4000K
Lichtbron(nen) : Epistar 2835
Lichtspreiding : 160°
Classificatie : IP65
Materiaal : ABS/PC
Afmetingen : 662x86x80mm
Garantie : 3 jaar

BoxLine Double 60
93070/71/75
230VAC
prismatisch mat
16watt
>0.9
1440lm
>80
3000/4000K
Epistar 2835
160°
IP65
ABS/PC
662x86x80mm
3 jaar

BoxLine Single 120
93120/21/25
230VAC
prismatisch mat
18watt
>0.9
1620lm
>80
3000/4000K
Epistar 2835
160°
IP65
ABS/PC
1272x86x80mm
3 jaar

BoxLine Double 120
93170/71/75
230VAC
prismatisch mat
36watt
>0.9
3240lm
>80
3000/4000K
Epistar 2835
160°
IP65
ABS/PC
1272x86x80mm
3 jaar

Optionele Noodstroomvoorziening;

Accupakket : Li-Ion
Autonomie : >90min
Test : handmatig
Visueel : laden / geladen / storing

Li-Ion
>90min
handmatig

Li-Ion
>90min
handmatig

Li-Ion
>90min
handmatig

Optionele Sensor ;

RadarWave : instelbaar
Stand-by functie : 10/20/30%
LDR : aan/10/30/50lux
Tijd 100% licht : 10sec/1/6/12min

instelbaar
10/20/30%
aan/10/30/50lux
10sec/1/6/12min

instelbaar
10/20/30%
aan/10/30/50lux
10sec/1/6/12min

instelbaar
10/20/30%
aan/10/30/50lux
10sec/1/6/12min